

△ M20X1.5-6H ISO (METRIC) THREAD
19,026/19,216 PITCH DIA.



**ALL O-RING "LEAD IN'S" TO
BE SMOOTH AND FREE OF NICKS
AND SHARP EDGES

PROPRIETARY NOTICE
THIS DRAWING DESCRIBES A
PROPRIETARY PRODUCT OF
SUN HYDRAULICS CORPORATION
AND MAY NOT BE REPRODUCED OR
GIVEN TO A THIRD PARTY WITHOUT
WRITTEN PERMISSION FROM
SUN HYDRAULICS CORPORATION
© SUN HYDRAULICS CORPORATION

						UNLESS OTHERWISE SPECIFIED			TITLE T-11 A CAVITY DIMENSIONS, TOOLING, PORTING		REVISION M	PART NO. T-11 A METRIC SHEET 2 of 3	
						DIM. TOLERANCE +/- .013 mm UNLESS SPECIFIED							
						ANGLE TOL ± 1/2 FINISH 20 ✓ UNLESS SPECIFIED REMOVE ALL BURRS							
						SCALE REF. 2 : 1		SERIES 1	MATERIAL				
						DRAWN HHP	CHECK JDA	RELEASE DATE	HEAT TREAT & FINISH 				
M	REVISED TOOLING P/N, REVISED DIMS FOR CAVITY/TOOLING CONSISTENCY	04MAY11	JRS	RCL	I0164								
LET	REVISION	DATE	DRN	CHK	REL								

REVISION	PART NO.	T-11A	METRIC
M		SHEET	2 of 3