



MODEL
CDAP

Mechanically-operated, back-to-back check valve
CAPACITY: 4,7 L/min. | CAVITY: T-162DP



CONFIGURATION

M	Control	Mechanical Actuation
C	Cracking Pressure	30 psi (2 bar)
N	Seal Material	Buna-N

The phaser check is a pair of checks, back-to-back, with the poppet at port 1 mechanically actuated. The valve is meant to be installed into the piston of a cylinder. When the cylinder reaches the end of its stroke the poppet in the phaser check is shoved off its seat allowing flow through the piston. This allows two cylinders to get back into phase.


TECHNICAL DATA

Cavity	T-162DP
Series	0
Capacity	4,7 L/min.
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Valve Internal Hex Size	8 mm
Valve Hex Size	19,1 mm
Valve Installation Torque	27 - 34 Nm
Seal kit - Cartridge	Buna: 990-162-007
Seal kit - Cartridge	Viton: 990-162-006
Model Weight	0.03 kg.

TECHNICAL FEATURES

- This valve is not designed to handle side forces. Actuating direction must be axial, and contact surface must be perpendicular to valve axis to within 5°.
- This valve is NOT meant to be cam operated.
- This valve is NOT to be used in place of a mechanical stop.
- Maximum stroke of the poppet must be limited to .047 in. (1,2 mm) by a mechanical stop other than the valve itself.
- Note: Port 2 of the T-162A cavity is not used with this valve.
- Check valves offer extremely low leakage rates with a maximum leakage of less than 1 drop per minute (0,07 cc/min).
- A cylinder that does its work while extending can put a large load on the rod gland at the end of its stroke. A phaser check in the piston can limit the unnecessary force on the gland.
- If you need to monitor the pressure in a cylinder, a phaser check can prevent the trapping of a false pressure value by a load holding valve.
- A phaser check in the piston of a vertically mounted cylinder will bleed air at the end of the stroke.
- Phaser checks in the pistons of master/slave cylinders will synchronize the cylinders simply by taking the mechanism to the end of its travel in both directions. This lends itself to dual cylinder steering applications.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES



CONFIGURATION OPTIONS

CONTROL

Standard Options	B	External 1/4 BSPP Port
	E	External 4-SAE Port
	M	Mechanical Actuation

CRACKING PRESSURE

Standard Options	C	30 psi (2 bar)
-------------------------	----------	----------------

SEAL MATERIAL

Standard Options	N	Buna-N
	V	Viton

Copyright © 2002-2014 Sun Hydraulics Corporation. All rights reserved.