


CSTFE...UK

NEW!

ПРОУШИНА
(НЕОБСЛУЖИВАЕМАЯ)



Обозн. Тип UK	Обозн. Тип UK...2RS	ØP	Z	S	D1	S1	L	F	LF мин.	FC (кН)	кг
CSTF1106UK		6	36	6	21	4.3	46.5	M6x1	18	3.6	0.01
CSTF1108UK		8	42	8	24	6.0	54.0	M8x1.25	22	5.8	0.03
CSTF1110UK		10	48	9	29	7.0	62.5	M10x1.5	27	8.6	0.05
CSTF1112UK		12	54	10	34	8.0	71.0	M12x1.75	30	11.4	0.08
CSTF1115UK		15	63	12	40	10.0	83.0	M14x2	34	17.6	0.14
CSTF1117UK	CSTF1117U2	17	69	14	46	11.0	92.0	M16x2	36	22.4	0.19
CSTF1120UK	CSTF1120U2	20	78	16	53	13.0	104.5	M20x1.5	43	31.5	0.31
CSTF1125UK	CSTF1125U2	25	94	20	64	17.0	126.0	M24x2	53	51.0	0.56
CSTF1130UK	CSTF1130U2	30	110	22	73	19.0	146.5	M30x2	65	65.5	0.89
	CSTF1135U2	35	140	25	82	21.0	181.0	M36x3	82	112.0	1.40
	CSTF1140U2	40	150	28	92	23.0	196.0	M39x3	86	140.0	1.80
	CSTF1145U2	45	163	32	102	27.0	218.0	M42x3	94	180.0	2.60
	CSTF1150U2	50	185	35	112	30.0	241.0	M45x3	106	220.0	3.40
	CSTF1160U2	60	210	44	135	38.0	277.5	M52x3	115	345.0	5.90
	CSTF1170U2	70	235	49	160	42.0	315.0	M56x4	125	440.0	8.20
	CSTF1180U2	80	270	55	180	47.0	360.0	M64x4	140	570.0	12.00



FC = МАКС. ДИНАМИЧЕСКАЯ НАГРУЗКА

МАТЕРИАЛ: СТАЛЬ ISO 12240-4 СЕРИЯ E Тип M

CSTFI...UK

NEW!

ПРОУШИНА
(НЕОБСЛУЖИВАЕМАЯ)



Обозн. Тип UK	Обозн. Тип UK...2RS	ØP	Z	S	D1	S1	L	F	LF мин.	FC (кН)	кг
CSTF1006UK		6	30	6	21	4.3	40.5	M6x1	11	3.6	0.02
CSTF1008UK		8	36	8	24	6.0	48.0	M8x1.25	15	5.8	0.04
CSTF1010UK		10	43	9	29	7.0	57.5	M10x1.5	20	8.6	0.06
CSTF1012UK		12	50	10	34	8.0	67.0	M12x1.75	24	11.4	0.09
CSTF1015UK		15	61	12	40	10.0	81.0	M14x2	30	17.6	0.18
CSTF1017UK	CSTF1017U2	17	67	14	46	11.0	90.0	M16x2	34	22.4	0.22
CSTF1020UK	CSTF1020U2	20	77	16	53	13.0	103.5	M20x1.5	40	31.5	0.35
CSTF1025UK	CSTF1025U2	25	94	20	64	17.0	126.0	M24x2	48	51.0	0.64
CSTF1030UK	CSTF1030U2	30	110	22	73	19.0	146.5	M30x2	56	65.5	0.93
	CSTF1035U2	35	125	25	82	21.0	166.0	M36x3	60	112.0	1.30
	CSTF1040U2	40	142	28	92	23.0	188.0	M39x3	67	140.0	2.01
	CSTF1045U2	45	145	32	102	27.0	196.0	M42x3	65	180.0	2.50
	CSTF1050U2	50	160	35	112	30.0	216.0	M45x3	69	220.0	3.50
	CSTF1060U2	60	175	44	135	38.0	242.0	M52x3	73	345.0	5.50
	CSTF1070U2	70	200	49	160	42.0	280.0	M56x4	80	440.0	8.60
	CSTF1080U2	80	230	55	180	47.0	320.0	M64x4	85	570.0	12.00

FC = МАКС. ДИНАМИЧЕСКАЯ НАГРУЗКА

МАТЕРИАЛ: СТАЛЬ ISO 12240-4 СЕРИЯ E Тип F